Unit 6 Weston Works, Weston Lane, Tyseley, Birmingham B11 3RP.
Tel. 0121 764 5600 Fax. 0121 764 5551 e-mail sales@birminghamtransformers.co.uk

SPECIFICATION FOR T STYLE ENCLOSURE

- 1) **Material**:- All lids, base and body are manufactured in Mild Steel. For thicknesses of lids base and body please refer to table below.
- 2) **Preparation**:- This enclosure is completely degreased and then has an iron phosphate treatment. Paint thickness onto of this is to a minimum of 70microns
- 3) Type of paint :- Epoxy polyester paint
- 4) Colour :-Pebble Grey RAL 7032
- 5) **Characteristics of paint material**:- Exhibits excellent mechanical strength & corrosion resistance. It is also chemically resistant to many acids, oils & solvents.
- 6) **Environmental use**: These cases are suitable for indoor use. Can obtain IP54 versions which are suitable for outdoor applications
- 7) **Mechanical**:- These cases are designed to be floor mounted . These enclosure are not designed to withstand large amounts of vibration or shock loads.
- 8) *IP rating*:- All our standard range of T style cases are rated at IP 22 protection. This range of cases can be modified to increase the IP rating to the customer requirements.

TABLE GIVING DETAILS OF PANEL THICKNESS FOR T RANGE OF ENCLOSURES

P DESIGNATION	THK OF SIDE PANELS (mm)	THK OF LID (mm)	THK OF BASE CHANNEL(mm)
Т3	1.5	1.5	3.0
T4	1.5	1.5	3.0
T5	1.5	1.5	3.0

Note:- Please refer to Birmingham Transformers Drawing No BTD-00057 for overall dimensions.

Photograph of T style Enclosure



